



<p><b>Product images</b></p>	
<p><b>Brief description</b></p>	<p>This speaker is specialized for deep bass reproduction and can be perfectly combined with the Ambientone panels No.4, No.2, and No.1. This hi-tech in-wall subwoofer features a very low structure-borne sound thanks to its special design. Wall vibrations and the transmission of noise to neighbouring rooms are therefore reduced to a minimum, even without additional decoupling. The front of the subwoofer consists of a gypsum plasterboard. In the same way as Ambientone No.4, it is screwed onto the substructure of drywall constructions and plastered over flush with the surrounding plasterboard. A 10 mm narrow slit acts as a sound outlet and can be positioned inconspicuously above the skirting board or close to the ceiling. The integrated special switch enables a direct connection to a standard amplifier.</p>
<p><b>Purchase order items</b></p>	<p>Scope of delivery</p> <ul style="list-style-type: none"> <li>• Subwoofer with connection cable</li> <li>• Installation instructions</li> </ul>
<p><b>Product diagram</b></p>	
<p><b>Technical data</b></p>	<ul style="list-style-type: none"> <li>• Design: Passive stereo system</li> <li>• Dimensions: 500 x 625 x 86 mm</li> <li>• Cutout: 435 x 570 mm</li> <li>• Installation depth: 73 mm</li> <li>• Power rating: 2 x 100 W max.</li> <li>• Impedance: 2 x 6 Ohm</li> <li>• Sensitivity: 82 dB (1 watt/1m)</li> <li>• Frequency range: 38–200 Hz</li> <li>• Max. acoustic pressure: 108 dB (1 watt/1 m)</li> <li>• Frequency crossover: Integrated special cross switch</li> <li>• Connection: 10 m loudspeaker cable</li> <li>• Conforms to CE: yes</li> <li>• Conforms to RoHS: yes</li> </ul>



<p><b>Handling and installation instructions</b></p>	<p>Generally, when installing built-in loudspeakers ensure that no loose screws or other parts can vibrate in the ceiling or wall construction and cause interference.</p> <p>Tape up the sound outlet slit, e.g. with masking tape, before sealing to prevent any compound from entering the subwoofer. Remove the masking tape after sealing and sanding smooth.</p>														
<p><b>Accessories</b></p>	<p>From the in-akustik cable range:</p> <ul style="list-style-type: none"> <li>• 003 021 Star loudspeaker cable 2 x 1.5 mm<sup>2</sup>, transparent</li> <li>• 003 02198 Star loudspeaker cable 2 x 1.5 mm<sup>2</sup>, transparent professional</li> <li>• 00402918 Premium loudspeaker cable HALOGENFREE 2 x 1.5 mm<sup>2</sup> round, grey 100</li> <li>• 004029188 Premium loudspeaker cable HALOGENFREE 2 x 1.5 mm<sup>2</sup> round, grey 500</li> <li>• 008 155 Premium flexible pin 1.5 qmm–4.0 qmm bulk</li> <li>• 008 1551 Premium flexible pin 1.5 qmm–4.0 qmm; set of 4, 50 pcs.</li> </ul>														
<p><b>Product benefits</b></p>	<ul style="list-style-type: none"> <li>• Virtually invisible subwoofer system</li> <li>• Low structure-borne sound</li> <li>• Driver unit can be exchanged for servicing</li> <li>• Width in standard drywall dimensions 625mm</li> <li>• Easy installation in normal drywall constructions</li> </ul>														
<p><b>Applications</b></p>	<ul style="list-style-type: none"> <li>• Bass loudspeaker for integration into drywall constructions</li> <li>• Perfect bass tone support e.g. for AmbientTone No. 4, e.g. for</li> <li>• Multi-room</li> <li>• Surround systems</li> <li>• Hospitality   Bar   Hotel</li> <li>• Conference facilities</li> <li>• Health facilities</li> <li>• and much more!</li> </ul>														
<p><b>Overview of items</b></p>	<table border="1"> <thead> <tr> <th colspan="4">AMBIENTONE SUB NO.2</th> </tr> <tr> <th>Item-no.</th> <th>Designation</th> <th>Unit</th> <th>SRP</th> </tr> </thead> <tbody> <tr> <td>0025201</td> <td>AmbienTone Sub No.2</td> <td>1 pc</td> <td>1999,00</td> </tr> </tbody> </table>			AMBIENTONE SUB NO.2				Item-no.	Designation	Unit	SRP	0025201	AmbienTone Sub No.2	1 pc	1999,00
AMBIENTONE SUB NO.2															
Item-no.	Designation	Unit	SRP												
0025201	AmbienTone Sub No.2	1 pc	1999,00												