

PRIMARE SP33 Specification sheet

| | | | |
|---------------------------|---|------------------------------|---|
| General | | Video | HDMI with HDvideo pass-tru and with 3Dpass and HDMI OSD OSD |
| Analogue Inputs | 2 Balanced, 8 RCA, incl 7.1 inputs | Upscaling | 1080p/24 |
| Digital Inputs | 1 Balanced, 3 RCA, 3 TOS-Link | | |
| Video Inputs | 5 HDMI | | |
| | | Other out-/inputs | 1 IR Input 3 12v outputs (triggers) 1 RS232 |
| Balanced Analogue outputs | Front (left and right) Center, Sub, Surr (left and right) Surr back (left and right) | Power Consumption operate: | <60W |
| RCA Analogue Outputs | Front (left and right) Center, Sub, Surr (left and right) Surr back (left and right) | Analogue Pre amp data | |
| Analogue Record | | | |
| Output | 1 RCA (left and right) | THD | <0.005%, 20 Hz-20kHz |
| Zone2 | 1 RCA (left and right) | Signal-to-Noise | -110 dB |
| | | Frequency Response | 10 Hz-100 kHz, 1dB |
| Digital Output | 1 RCA, 1TOS-Link | Input Impedance | 47 K Ω , unbalanced |
| Video Output | 2 HDMI – individual settings | Input Impedance | 3 K Ω , balanced |
| | | Output Impedance | 47 R unbalanced |
| Modes | Stereo Bypass Party Dolby Prologic IIx Music Dolby Prologic IIx Movie DTS NEO:6 MUSIC DTS NEO:6 CINEMA | Digital Data | 47R Balanced |
| | | Frequency Response | 20 Hz-20 kHz+ 0.2dB |
| | | THD+Noise | 0,005% @1 kHz(AES17 filter) |
| Decoding Formats | Dolby TrueHD Dolby Digital Dolby Digital EX Dolby Prologic II Dolby Prologic IIx DTS-HD Master Audio DTS DTS ES DTS Neo:6 DTS 96/24 MULTI/2 CH PCM/LPCM | Dimensions (WxDxH) | 430 x 385 x 180 mm |
| | | Weight | 12 Kg |
| Samping rates | 32KHz,44.1KHz,48KHz, 88.2KHz,96KHz,192KHz (AES/EBU) | | |